

Jata Sheet

EFG-02 E-Field Generator

Product Overview

Performance The TDK EFG-02 is a transmission-line type electric/magnetic field generator which provides an unprecedented level of flexibility in the generation of controlled, high-intensity electric and magnetic fields over the frequency range of 10 kHz to 100 MHz. It is capable of generating over 500 V/m over its entire operating frequency range using 2.5 kW amplifier and provides a large uniform field area, thus accommodating a very large variety of DUTs.

Non-Radiating Because the EFG-02 is a non-radiating device, the electric and magnetic fields are essentially confined to the DUT area. Also, it provides extremely low VSWR over its entire operating range thus reducing stress on the amplifier.

Unique Design The unique mechanical design of the EFG-02 greatly facilitates the characterization of unwieldy DUTs. Large or bulky DUTs can simply be wheeled or placed under the system with the aid of equipment (such as a pallet jack or forklift).



The ability generate controlled, high-intensity electric and magnetic fields over the frequency range of 10 kHz to 100 MHz and a unique design make the EFG-02 the best choice for conducting immunity testing on large, heavy, or bulky DUTs.

Features

- 10kHz 100 MHz operating range
- High power field generator
- Up to 500 V/m RSM
- Low VSWR
- Adjustable height for optimizing performance

Applications

 Immunity testing on Large, heavy or bulky DUTs



EFG-02 E-Field Generator

Mechanical Specifications

Height: 195.6 cm (77 in.)

Length: 335.3 cm (132 in.)

Width: 76.2 cm (30 in.)

Construction: Fiberglass and PVC

Input Connector: 7/16 female

Electrical Specifications

Input Power: 3500 W maximum con-

tinuous

Operation Frequency:

Range: 10 kHz - 100 MHz

Input Impedance: 50Ω nominal

Field Strength: Up to 500 v/M RMS

Ordering Information

Product: E-Field Generator

Model Number: EFG-02 Warranty: 1 year

To place an order or to learn more about the TDK products that best meet your needs, contact your TDK sales representative:

TDK RF Solutions Inc.

1101 Cypress Creek Rd. Cedar Park, Texas 78613 USA

Phone: 1-512-258-9478 Fax: 1-512-258-0740

E-mail: info@tdkrf.com
World Wide Web: www.tdkrfsolutions.com

Environmental Specifications

Ambient Temperature Limits:

Operating: 0° to $+40^{\circ}$ C Storage: -10° to $+50^{\circ}$ C

S C P SW TS
SYSTEMS CHAMBERS PRODUCTS SOFTWARE TEST SERVICES

www.tdkrfsolutions.com