

TRI-350R Adjustable Tripod

Product Overview

The TDK TRI-350R tripod is a sturdy, lightweight, portable, non-conductive tripod designed specifically for mounting antennas and video cameras in EMC test environments.

The tripod is constructed of light but strong fiberglass and plastic to provide the necessary stability while allowing for lightweight portability.

The tripod easily adjusts from 65 cm to 160 cm in height and supports equipment up to 15 kg. The sturdy, fixed-length fiberglass legs feature smooth-rolling lockable caster wheels for easy maneuverability. If preferred, fixed adjustable rubber foot pads can be optioned to accommodate uneven floor surfaces. The tripod legs fold inward for storage or transportation between test sites.

The TRI-350R is available with a variety of antenna and video camera mount adapters to meet your requirements.

Features

- Made of non-conductive materials
- 1/4-20" screw mount adapter (standard)
- Supports up to 15 kg (33 lbs)
- Low height setting by removing a section of the modular center pole
- Internal cable routing through center pole
- Smooth-rolling, lockable caster wheels
- Compact shipping box

Options

- Fixed rubber feet can be specified in place of wheels
- Custom antenna mount adapters available
- Remote controlled Pneumatic Polarization feature available



The TDK TRI-350R Tripod is a lightweight tripod designed for EMC test environments to hold cameras, antennas and other test equipment.

Applications

- Antenna mounting
- Video camera mounting
- Apparatus mounting

TRI-350R Adjustable Tripod

Mechanical Specifications

Dimensions:

Extended Height: 160 cm (63.0 in)

Collapsed Height: 65 cm (25.6 in)

Base Diameter: 86 cm (33.8 in)

Weight: 4.2 kg (9.2 lbs)

Construction: Fiberglass and plastic

Finish: Preventive water absorption seal



Removing a section of the modular center pole allows a low height setting.

Ordering Information

Product: Tripod
Model Number: TRI-350R
Warranty: 1 year

To place an order or to learn more about the TDK products that best meet your needs, contact your TDK sales representative:

TDK RF Solutions Inc.

1101 Cypress Creek Rd.
Cedar Park, Texas 78613 USA
Phone: 1-512-258-9478
Fax: 1-512-258-0740
E-mail: info@tdkrf.com
World Wide Web: www.tdkrfolutions.com



Cabling can be routed through the center pole.



Tripod quickly dismantles for compact, light-weight transportation.

TOTAL RF EXPERTISE™



www.tdkrfolutions.com

To learn more about TDK's wide range of innovative test products, solutions and services visit www.tdkrfolutions.com

Copyright © TDK RF Solutions Inc. All rights reserved. Specifications subject to change without notice.

Rev. 2017-07-18